



CO₂ Capture Project



Capture Technology Overview

EU Roll-out
Bruxelles, June 2nd, 2004



CO₂ Capture Project



**US Department
of Energy**



**European
Union**




**Klimatek
NorCap**



CO₂ Capture Project


The three options





CO₂ Capture Project

TOTAL FUNDING ~ 25 MMUS\$



- Pre-Combustion
- Oxyfuel
- Post-combustion
- Storage
- Economics
- Cost estimating



CO₂ Capture Project

Scenario	Fuel	CO ₂ Source	CO ₂ Sink	Capture Target (MM tonne/yr)
Grangemouth Refinery in Scotland	Gas and Fuel Oil	Flue gas from heaters and boilers	Offshore EOR	2.0
Norway 385-MW power plant in Karsto, Norway	Gas	Flue gas from turbine outlet	Offshore EOR	1.1
Alaska Eleven 30-MW single cycle gas turbines.	Gas	Flue gas from distributed turbines	Onshore EOR	1.8
Canada Gasification plant	Pet Coke	Syngas from gasifier	Onshore EOR	6.8





Post-Combustion Overview

The Team:

Odd Furueth

Daniel Chinn

Paul Hurst

Dag Eimer

Mariette Knaap

Piergiorgio Zappelli



CO₂ Capture Project

Post-Combustion: The Baselines

- **North European Refining and Petrochemical Complex.**
 - Amine Baseline Study to capture 2 million tpa CO₂ from heaters and boilers across the complex - with Fluor
- **Alaska Open Cycle Gas Turbines.**
 - Amine Baseline Study to capture 2 million tpa CO₂ from 11 open cycle gas turbine sets - with Fluor
- **Norwegian 400MW power plant**
 - Amine Baseline study to capture 1 million tpa CO₂ from power plant exhaust gases – with Fluor
- **Canadian Coal Gasification Plant**
 - Selexol Baseline study to capture 6.8 million tpa CO₂ from syngas – with Fluor





CO₂ Capture Project


Key Outcomes – Absorption Based Technologies

- **Baseline studies...**

- Have established the technical feasibility and costs of post combustion CO₂ capture across scenarios.
- Highly energy intensive process...
- Technology largely proven (albeit not at this scale) and available today for retrofit.
- Requires coincidental removal of SO_x and NO_x (amine)
- It is high capital cost.

- **Key Issues are...**

- Low CO₂ concentration in flue gas
- Low pressure flue gas
- Large volumes of flue gas being handled





CO₂ Capture Project

Post-Combustion Baseline Costs

Scenario	Incremental Capital Cost MMUS\$	CO ₂ Captured MMT/year	CO ₂ Avoided MMT/year	CO ₂ Avoided Cost (US\$/ton)
Grangemouth Refinery in Scotland	362	2.19	1.55	78.1
Norway 385-MW power plant in Karsto, Norway	323	1.09	0.87	61.6
Alaska Eleven 30-MW single cycle gas turbines.	1012	1.90	1.96	88.2
Canada Gasification plant	519	6.80	5.22	14.5





CO₂ Capture Project

Technology Areas Reviewed by the CCP

• **Absorption Processes**

- Traditional Amine based – low cost & integrated designs.
- Membrane based – using proprietary solvents.

• **Adsorption Processes**

- PSA – using novel materials.
- ESA – using carbon fiber composite mol sieve.

• **Other Processes**

- Cryogenics
- Compact Equipment Designs
- Novel Concepts





CO₂ Capture Project

Key Outcomes – Absorption Based Technologies

Amine Absorption Low Cost and Integrated Designs (Norway CCGT Power Plant).

- **Nexant Low Cost Design**

Identify ideas for design simplification/cost reduction of post combustion CO₂ capture using amines (retrofit emphasis)

- **Nexant Integrated Design**

Identify ideas for design and integration of post combustion CO₂ capture with new build CCGT.

- **Combination MHI & Nexant (CCP ‘BIT’)**

Application of design philosophy from Nexant (simplified and integrated studies) in conjunction with MHI’s KS-1 solvent.





CO₂ Capture Project

The Elements of Low-Cost Design


- No flue-gas cooler (absorber feed temperature of 80°C).
- Down-grading of gas blower and pumps.
- Plate & Frame exchangers rather than Shell & Tube.
- Structured packing rather than random.
- Lower overall reboiler by adding a vapor recovery system and live steam from HRSG.
- **Only for the BIT-case:** Solvent KS-1 by MHI rather than MEA (25% lower regeneration energy).





CO₂ Capture Project


Low-Cost Capture Plant





CO₂ Capture Project

BIT Integrated (Note: Solvent switched to KS-1)





CO₂ Capture Project

Summary of Cost and Performance (by CCP)

	Net Power (MW)	Efficiency (%)	USGC Capex (\$MM)	USGC Opex (\$MM/yr)	USGC CO₂ Avoided Cost (\$/tonne)
Uncontrolled	392	57.6	284	13	N/A
Base Capture	322	47.3	418	26	60.0
Low-Cost Capture	332	48.8	366	24	44.7
Low-Cost Integrated	335	50.6	345	24	35.1
BIT	357	52.5	352	21	28.2





CO₂ Capture Project

BIT Conclusions

- BIT evolved from several, independent CCP projects
- Significant Cost-Reduction Potential (~50%)
- Further engineering work with turbine vendor needed
- Pilot testing for cost-saving ideas needed
- Improvements in solvents can improve BIT further
- Possible concern: acceptance of integration



MHI / Kvaerner membrane contactor

- To develop an optimised process for CO₂ removal from flue gas
- By piloting the combination of Kvaerner's membrane contactor & MHI's KS-1 solvent technology

Kvaerner
membrane

+


KS-1
solvent

+

MHI Nanko
test facility

=


Pilot Demo
in Japan





MHI / Kvaerner membrane contactor

- In the membrane gas/liquid contactor:
- Membrane physically separates flue gas containing 3 to 10% CO₂ from the KS-1 solvent
- Mass transfer of CO₂ occurs across the membrane due to absorption



Key Issue : Amine solvent migrates through the membrane requiring an additional flue gas clean up step.



CO₂ Capture Project

Key Outcomes – MHI/Kvaerner Membrane

- Capital cost saving (versus conventional absorber/desorber equipment) are small and within the accuracy of the estimating technique.
- The principal advantage with this combination lies in the lower energy consumption of the KS-1 solvent (25% lower than MEA). Lower operating cost.
- The membrane system has a much smaller footprint and a much lower weight than conventional equipment. It will have an advantage where space and weight are at a premium....offshore.
- Reduction (versus baseline) in Cost of CO₂ Capture is 19%. Majority of this comes from operating cost reduction.







CO₂ Capture Project

Key Outcomes – Adsorption Based Technologies

Two key Studies undertaken by the CCP

- SRI : Self Assembled Nanoporous materials.
 - Uses Copper Dicarboxylate materials.


- ORNL : Electric Swing Adsorption
 - Uses Carbon Fiber Composite Molecular Sieve material.





CO₂ Capture Project

PSA/ESA Process Flow scheme





CO₂ Capture Project

SRI : Self-Assembled Nanoporous Materials for CO₂ Capture..... Key Outcomes

- Simulation of a two-bed PSA system designed for a 400 MW gas fired power plant.
- Adsorption at exhaust gas pressure; desorption under vacuum.
- Recovery of 34.1% CO₂ at 67.9% purity.
- Sorbent weight:

	Cost (per ton CO ₂ captured):
• SRI powder; 2,881 kg/bed;	SRI powder, \$ 406.5
•SRI granulated; 5,549 kg/bed;	SRI granulated, \$495
•HISIV; 1,440 kg/bed.	HISIV, \$ 393.
- Power requirement for CO₂ capture: 1 GW.





CO₂ Capture Project



ORNL : CFCMS material used with ESA for CO₂ Capture..... Key Outcomes

- CCP Internal engineering and cost review (Post Combustion at commercial scale) suggests 'no cost reduction potential' versus baseline amine technology.
- Low CO₂ loading on CFCMS requires multiple large Adsorber vessels and large CFCMS quantities.
- CFCMS pressure loss high – requires significant reduction for commercial feasibility.
- Requirement for substantial flue gas blower and regeneration vacuum systems – with attendant high cost.

Adsorbent systems all seem to suffer the same key problems;

- Low CO₂ loading due to low operating pressure
- Requirement to operate desorption under vacuum conditions





CO₂ Capture Project

Other Processes and Novel Concepts

- Cryogenic Processes were rejected for study early on;
 - Drying
 - Freezing
- CO₂ hydrate briefly considered but cooling needs and partial pressure requirements appeared to make this impractical.
- Compact Equipment (Rotating Absorber/Desorber) was considered but development cost and schedule did not match available funds or timing for the CCP.
- Novel Chemistry approaches have been considered more recently, with pH swing and melting point swing processes planned for future evaluation.





CO₂ Capture Project

Oxyfuel Overview

The Team:

John Boden

Ivano Miracca

Knut Ingvar Aasen

Tom Brownscombe

Karl Gerdes

Francesco Saviano

Mark Simmonds





CO₂ Capture Project

Oxyfiring: Combustion with “pure” oxygen

- **Oxyfiring not currently used in typical large combustion systems because of:**
 - ❖ **Expensive air separation system.**
 - ❖ **Necessity of flue gas recycle to moderate temperature.**
- **In the perspective of CO₂ capture, oxyfiring has the unique advantage to generate an effluent stream almost exclusively composed by CO₂ and H₂O resulting in cheap and easy capture.**



CO₂ Capture Project

Oxyfuel: The Background

- **Cryogenic air separation is a mature technology with very little possible improvement.**
- **Large R&D ongoing Projects to develop novel “breakthrough” technologies for air separation with the target of commercialization by 2008-2010.**
- **Research in the field largely independent from “greenhouse gases” concerns.**





CO₂ Capture Project

Oxyfuel Scope of Work

- **Definition of an Oxyfuel Baseline by application of “state-of-the-art” technologies to the European Refinery Scenario.**


- **Investigation of the technical/economical potential of novel technologies or equipment, particularly:**
 - ❖ **Novel technological solutions for boiler revamping or new-building, maintaining cryogenic air separation (heaters have more uncertainties).**
 - ❖ **Advanced thermodynamic cycles for oxyfiring in power generation systems.**
 - ❖ **Novel air separation technologies for application to conventional boilers/heaters systems.**
 - ❖ **Novel technologies integrating steam or power generation systems and novel techniques for oxygen supply.**





CO₂ Capture Project

The Oxyfuel Baseline(1)





CO₂ Capture Project

The Oxyfuel Baseline(2): Economics

	Post Comb. Baseline	Case 1: Cryogenic O ₂ Base Case	Case 2: Cryogenic O ₂ & offset steam	Case 3: Cryogenic O ₂ & offset steam via H ₂
Captured CO ₂ (MMtons/year)	2.0	1.88	1.69	2.33
Avoided CO ₂ (MMtons/year)	1.4	1.65	1.57	1.99
CO ₂ Captured Cost (US\$/ton)	55	38.0 (- 30.9%)	36.1 (- 34.4%)	33.8 (- 38.5%)
CO ₂ Avoided Cost (US\$/ton)	78	43.2 (- 44.6%)	38.9 (- 50.1%)	39.3 (- 49.6%)
Power Export (MWe)	Utility Neutral	10.7	3.4	(0.3)

➤ Alignment by the CEM Team for Case 1 resulted in : CO₂ capture cost: 44.4 US\$/ton
CO₂ avoided cost: 49.3 US\$/ton



Further 10\$ reduction if NO_x credit is accounted for.





CO₂ Capture Project

The Oxyfuel Baseline(3): Main Conclusions

- **Conversion of heaters and boilers to oxyfiring is technically feasible.**
- **Economic optimum for oxygen purity of 95%.**
- **Transport of concentrated O₂ raises additional (manageable) safety issues.**
- **One order of magnitude reduction in NO_x emissions is also achieved.**

- **The Oxyfuel Baseline is applicable with consistent saving compared to any other available options, and low technical risk, so that implementation in Countries applying high level of Carbon Tax may be considered.**



CO₂ Capture Project

Novel boilers optimized for Oxyfiring of fuel gas or oil

➤ **A few studies were commissioned to different Technology Providers to investigate potential savings achievable by optimization of boilers for oxyfiring:**

❖ **High Pressure Boiler – Mitsui Babcock.**

Expected savings by reduced volume and power consumption.

❖ **Staged Combustion Boiler – Mitsui Babcock.**

25% reduction in fuel gas recycle at the expense of doubled footprint.

❖ **Zero recycle Boiler – Alstom/Praxair.**

No fuel gas recycle by using higher grade materials.

➤ **No potential detected for consistent reduction in capture costs.**





Advanced Oxyfuel Thermodynamic Cycles (1)

- **Evaluation by SINTEF of three different power generation concepts from the scientific literature based on stoichiometric oxygen combustion of Natural Gas and claiming high thermodynamic efficiency, to avoid the penalties related to air compression for separation and flue gas recycle:**
 - ❖ **Water Cycle, using water injection rather than Flue Gas Recycle to control combustion temperature.**
 - ❖ **Graz Cycle, similar to Water Cycle, with steam injection in the combustor.**
 - ❖ **Matiant Cycle, based on high temperature turbine and heat exchangers.**



Advanced Oxyfuel Thermodynamic Cycles (2)

- **Main conclusion is that the high efficiency claimed by all of the studied cycles are related to features requiring significant developments in gas turbine / steam cycle equipment, e.g.:**
 - ❖ **High temperature operation (turbine inlet at 1500°C or heat exchanged at 1000°C).**
 - ❖ **Low vacuum condensing (0.06 bara).**
- **All the cycles were about the same efficiency when compared on consistent bases.**
- **Turbine vendors not willing to engage in very expensive development without clear market perspectives.**



CO₂ Capture Project

Novel Technologies for Air Separation


- Different Consortia are developing ionic transport membranes for air separation with DOE and EU-funding for commercialization by 2008-2010

Ion Transport Membranes (ITM) Oxygen Permeable Ceramics

Typical ITM

- ◆ Multi-component metallic oxide - mixed conductor

- = lanthanide ion
- = transition metal ion
- = oxygen ion, O²⁻
- = oxygen ion vacancy



Vacancies built into the oxide by ion substitution

- ◆ Mobile at >700°C

Oxygen permeates at high flux and 100% selectivity


- ◆ Dependent on integrity of seals and membrane



CO₂ Capture Project



Application of ITM (Air Products) in European Refinery





CO₂ Capture Project

Economics of ITM in European refinery

Case	GT	O ₂ reqd. Te/day	Total Power Reqd. (MW)	Export Power (MW)	CO ₂ Captured (x 10 ⁶ te/yr)	CO ₂ Avoided (x 10 ⁶ te/yr)
1	2 x V94.2	6626	54.7	446.2	1.89 / \$33.5	1.71 / \$37.0
2	2 x V94.2	3828	26.4	289.9	1.09 / \$25.1	1.43 / \$20.0
3	1 x V94.3	6051	71.3	121.4	2.62 / \$28.5	2.06 / \$38.1

- **CCP alignment of Case 1 at about 30 US\$/ton.**
- **Process scheme not fit for revamping unless there is market for power export.**
- **Promising option for new-built including CCGT systems for power generation.**






CO₂ Capture Project

Novel integrated equipment - AZEP (Advanced Zero Emission Power)


- AZEP is developed by Alstom/Norsk Hydro in the frame of a 3-years EU-funded Project started in January 2002.
- Technology is applicable to the CCP power generation Case Studies.
- Alaskan scenario was selected for the CCP study, since it is composed by relatively simple and small turbine systems.
- While the original concept calls for complete CO₂ capture, the CCP study also includes options with 80-90% capture that may minimize the CO₂ avoided costs.





CO₂ Capture Project



AZEP : The Process Scheme





CO₂ Capture Project

AZEP : Technical/Economical output






CO₂ Capture Project

Praxair advanced boiler

➤ Praxair is developing an advanced boiler, incorporating the OTM membranes in the frame of a DOE-funded Project whose target is achieving Proof-of-concept by 2006. The CCP and the DOE co-funded a study for application of the concept to replacement of a single boiler in the European Refinery Case Study.





CO₂ Capture Project

Praxair advanced boiler: economic results

- **Boiler capital cost ~ 40% higher than conventional boilers.**
- **Total capital ~ 60% lower than conventional boilers with Post-combustion capture.**
- **Rough estimate based on Praxair data on CO₂ capture cost at 15-20 \$/ton.**
- **Concept still at an early stage of development: commercialization expected by 2009-2010.**







CO₂ Capture Project

Chemical Looping

➤ Chemical Looping is a new combustion technology based on oxygen transfer from combustion air to the fuel by means of a metal oxide acting as a solid carrier. Core of the technology is a two-reactors system with continuous circulation of solids:





CO₂ Capture Project

Chemical Looping (2)

- Technology under development in the frame of the GRACE Project co-funded by DOE and EU with a budget of 1.5 MM€ (1/2002 – 12/2003).
- Consortium formed By BP (Coordinator), Alstom Boilers, Chalmers University, Vienna University and CSIC (Consejo Superior de Investigaciones Scientificas).
- Achieved proof-of-feasibility of the Technology through successful operation of a pilot unit reproducing the features of future commercial units, at Chalmers. Alstom developed PFD, main equipment sizing and preliminary economic evaluation.
- R&D activity was limited to atmospheric pressure applications using Natural Gas as fuel. This technology may however be also applied to the typical pressure of combined cycles for power generation (20-30 bars), as studied in a DOE funded Project (outside CCP).
- Commercialization expected by 2010-2012 after operation of demo-unit (1MW) by 2008 and implementation of small commercial unit (40-50 MW).





CO₂ Capture Project

Chemical Looping: main technical achievements

➤ **Proof-of-feasibility on pilot unit with continuous solid circulation and Ni- based carrier, including:**

- ❖ **Reversible reduction/oxidation of the solid and oxygen transfer.**
- ❖ **Almost complete methane combustion (99.5% at 800°C).**
- ❖ **No gas leakage between reactors.**
- ❖ **CO₂ purity > 98% (impurities by equilibrium CO and H₂).**
- ❖ **Achieved solid circulation rate and reaction rate according to the hypotheses for economical evaluation.**
- ❖ **No significant particle attrition or chemical decay observed.**





CO₂ Capture Project

Chemical Looping: remaining uncertainties

- **Major concerns to be defined by further R&D are:**
 - ❖ **Catalyst ageing, both chemical and mechanical.**
 - ❖ **Scale-up of catalyst manufacturing procedure.**
- **Once material issues are solved, scale-up risk is moderate due to similarity with existing commercial technology (CFB).**
- **Possible application to high pressure**



CO₂ Capture Project



Oxyfuel Key Outcomes

- **Oxy-firing offers the benefit to generate a flue gas stream containing only CO₂ and H₂O, making capture easy and inexpensive.**
 - ❖ **Oxy-firing can be practiced today using conventional air separation, along with flue gas recycle, in retrofit or new-built boilers and heaters at a cost of CO₂ avoided about 30% less than the Post-Combustion Baseline.**
 - ❖ **In the longer term (2008-2010), CO₂ avoided cost through Oxy-firing might be substantially reduced by advanced air separation technologies based on high temperature ceramic membranes, to the 20-30 \$/ton range.**
 - ❖ **CCP identified Chemical Looping as a technology with the same potential for cost reduction than ceramic membranes in the 2010 time frame and co-funded a EU Project which achieved Proof-of-Feasibility through pilot plant operation.**
 - ❖ **An additional benefit of Oxy-firing is the drastic reduction (>90%) of NO_x emissions.**
 - ❖ **Application with (gas) turbines requires further significant development to deal with the high temperature from this process.**





CO₂ Capture Project

Pre-Combustion Overview

The Team:

Henryk Andersen

Jan Assink

Cliff Lowe

Peter Middleton

Gabriele Clerici


Jan Schelling





CO₂ Capture Project

Pre-Combustion: the road through hydrogen





CO₂ Capture Project

PCDC advantages...

- CO₂ removal via solvent absorption is proven
 - ❖ Elevated pressures and high CO₂ concentrations aid removal
- Possible production of CO₂ at moderate pressures (lower compression costs)
- Produces hydrogen
- Low SO_x, NO_x
- Flexible fuel sources (gas, oil, coke, coal, etc.)





CO₂ Capture Project



.... and disadvantages

- Must convert fuel to syngas first.
- Requires major modifications to existing plants.
- Gas turbines, heaters, boilers, must be modified for hydrogen firing.



CO₂ Capture Project

Precombustion Work Scope

- Verify potential benefits and define performance targets.
- Evaluate improvement of baseline through standardization and large capacity plants.
- Investigation of the technical/economical potential of novel technologies:
 - CO₂ removal tailored to PCDC (CO₂LDSEP by Fluor).
 - Integration of WGS and CO₂ removal (MWGS, SEWGS).
 - Integration of syngas preparation and CO₂ removal (HMR).
 - Complete integration in a single unit (IFE).
- Evaluate enabling technologies (e.g. gas turbine firing with hydrogen).

- **Four large R&D Projects directly co-funded (with EU, DOE and Klimatek).**





CO₂ Capture Project

Review and Evaluation Studies

• **Advanced syngas study – Foster Wheeler**

- 400 MWe natural gas combined cycle power plant
- Seven PCDC process schemes evaluated
- No significant advantages over base PCDC plant

• **Hydrogen membrane study – Haldor Topsoe**

- Membrane reforming, membrane water gas shift
- Established targets for membrane performance
- Verified potential cost savings
- Showed disadvantage of upstream sulfur removal for coal gasification.





CO₂ Capture Project

Possible improvements through standardization or large capacity

• **Very Large Scale ATR (by Jacobs)**

- Single train production of H₂/N₂ mixture to support 1200 MWth of power.
- 90% CO₂ Capture by MDEA washing.
- < 20% improvement over baseline in CO₂ capture cost.

• **Standardized PCDC (by Jacobs)**

- Standardization for integration in CCGT systems.
- Modular design/construction, multiple identical units....
- 15-20% cost reduction by 10th Unit.





CO₂ Capture Project



CO₂LDSEP: Potential best fit for coal gasification.....

- Simultaneously produces H₂ and CO₂.
- Compressed feed gas enters an autorefrigeration plant where the CO₂ is liquefied in an expander
- Sulphur tolerant, H₂ delivered at pressure, high carbon recovery, high purity of CO₂
- Fluor has patented the process for use, among other things, in the recovery of CO₂ from hydrogen plant offgas, as well as from IGCC syngas
- Uses proven equipment and processes in a novel application (i.e. low technical risk)





CO₂ Capture Project

.....but no clear advantages over standard washing (Selexol)


- Petcoke gasification unit in Canada co-produces hydrogen, steam and power (total of about 600MWe equivalent).
- As compared to the controlled baseline the CO₂LDSep process requires less energy and generates an additional 35 MW of electrical power.
- Capex higher than baseline.
- Avoided and capture costs slightly lower than baseline in Case Study with very low costs (less than 15 \$/ton).
- Capex reduction might be achieved by relaxing CO₂ recovery requirement.





CO₂ Capture Project


Integration between WGS and CO₂ capture





CO₂ Capture Project

MWGS Reactor Concept



Water gas shift





CO₂ Capture Project

EU Grace MWGS Overview

- Two year EU/CCP co-funded Project to develop a highly selective hydrogen membrane for a water gas shift reactor (BP, Norsk Hydro, SINTEF, Univ. Twente, KTH, Univ. Zaragoza, IRMERC).

- Dense membrane - SINTEF


- 1-3 μm Pd/Ag alloy foil sputtered on single crystal silicon
- Foil deposited on porous stainless steel support tubes
- Tested at transmembrane pressure up to 15 bar
- H₂ permeance up to $3 \cdot 10^{-6}$ mol/(m² s Pa) at 300°C
- N₂ permeation not detectable – perfect selectivity
- Leak testing and repair technique developed





CO₂ Capture Project


Proposed process scheme





CO₂ Capture Project

Membrane Module Design





CO₂ Capture Project

DOE MWGS Overview

- 12 month work period beginning 3/2002
- Four sulfur tolerant membrane development programs
 - Silica, ECN
 - Zeolite, University of Cincinnati
 - Palladium alloy, CSM/TDA
 - Ceramic metal composite, Eltron
- Failure to develop sulfur tolerant membrane
 - Either inadequate H₂/CO₂ selectivity or intolerance to H₂S
- Membrane simulation model developed by ECN
- Eltron developed promising metal alloy membrane for sweet syngas





CO₂ Capture Project

DOE MWGS Overview – Phase 2

- **Eltron membrane development program**
 - **Focus on metal alloy membrane for sweet syngas**
 - **Significant improvement in flux/permeance**
 - **Two orders of magnitude improvement in flux over current state of the art (25 micron Pd)**
 - **Proof of concept testing successfully completed at ambient pressures**
- **SOFCo commercial MWGS reactor design**
 - **Innovative corrugated, planar design with stainless steel supports**
 - **Estimated costs is ~8% of the cost estimated in the Haldor Topsoe screening study for a 25 micron thick Pd membrane.**





CO₂ Capture Project

MWGS Conclusions

- **Pre-Combustion Decarbonisation by Membrane Shift Reaction is technically feasible**
 - **Both Eltron and Sintef membranes look promising with 7-8 years estimated time to commercial demonstration.**
- **Sequential reaction/separation lower risk**
- **The efficiency of CO₂ capture for the process is higher than the baseline.**
- **Capital cost significantly lower than baseline.**
- **Cost of CO₂ avoided in the European Refinery case, significantly lower than baseline (- 35-40%).**





CO₂ Capture Project

Sorption Enhanced WGS Overview

- Technology under development by Air Products coupling WGS and CO₂ adsorption in a single vessel with cyclic regeneration for CO₂ recovery.
- Total Budget \$1.2M (CCP/DOE)
- Test rig constructed
- Experimental programme run
 - a. Adsorption tests
 - b. Combined adsorption and reaction 'Proof-of-Concept'
- Capture schemes developed for Alaskan and Norwegian Case Studies.







CO₂ Capture Project

SEWGS vs, Conventional

Conventional System



SEWGS System



Similar benefits to MWGS





CO₂ Capture Project



SEWGS main conclusions

- SEWGS Concept proven – CO slip dropped by about 80%.
- Avoided CO₂ Cost reductions based on achieved results in Norwegian Case > 40%.
- Overall efficiency from 56% to 48.2%.
- Technology relatively low risk & short timescale compared to membranes.
- NO_x emission reductions possible to <25ppm
- Possible further savings by developing better adsorbents.
- Time to commercial demo estimated in 5-6 years.





CO₂ Capture Project

Hydrogen Membrane Reforming

- A 2.5 year and 1.9 mil US\$ project funded by Klimatek (52%).
- Vendors: Norsk Hydro, Sintef and UiO
- Tasks:
 - ❖ Ceramic Conducting Materials
 - ❖ Reactor design
 - ❖ Process design
- Target:

Develop Mixed Conducting Membrane (MCM) with sufficient H₂ transport rates and stability under selected process conditions. Develop a technoeconomically viable PCDC process including said materials.






CO₂ Capture Project

Hydrogen Membrane Reformer: The Concept

- Combination of reforming reactor and separation
- Extract product gas (H₂) from reactor, no traditional CO₂ removal system required
- Drive equilibrium limited reactions towards completion
- Expand allowed range of temperatures and pressures





CO₂ Capture Project

Overall membrane performance



- Experiments/model predict hydrogen flux above target
 - Scatter not yet fully understood
- Model predicts stability in process above 750°C
 - May be further improved
- Excellent high temperature stability
 - melts at around 2000°C, sinters >1700°C
 - high temperature creep unlikely to limit life time
- Excellent stability at low oxygen partial pressure in H₂ and natural gas.







CO₂ Capture Project

H₂ Generator System step 1 & 2



3 Sweep






CO₂ Capture Project



H₂ Membrane Reformer - Power Plant





CO₂ Capture Project


Process development summary

- **Potential CO₂ capture cost reduction in CCGT by 50 % Vs Baseline.**
- **5 ppm NO_x emission can be achieved without catalytic NO_x reduction.**
- **Loss in efficiency only 5%-points (vs. conv. CCGT).**
- **CO₂ emission close to zero.**
- **Compact Hydrogen Plant: Only 20 x 80 m (plot plan).**
- **Longer time (and costs) to market than other technologies. Pilot scale in operation by 2007-2008 and demo-unit by 2012-2013.**



CO₂ Capture Project

The IFE Concept: Complete Integration



Reforming:

$$\text{H}_2\text{O} : \text{CH}_4 = 3.5 / 2$$

$$\text{CaO} : \text{CH}_4 = 1.5$$

T = 600 °C

p = 5 bar

Calcination:

T = 1000 °C

p = 5 bar

Atmosphere = CO₂





CO₂ Capture Project

IFE Conclusions

- 90% CO₂ removal is possible
- CCPP with electrical efficiency 58% (LHV) is reduced to 40 - 44%
 - IFE CO₂-capture concept is intended to operate at lower pressures, H₂-fuel has to be compressed
 - Need for sulphur removal
- Producing H₂ for a steam boiler, waste heat is also generated
 - Heat can be used for preheating the boiler

**Due to very poor efficiency the team
agreed not to pursue this concept further**





CO₂ Capture Project

PCDC Key Outcomes

- Advanced Pre-combustion technology offers significant long-term cost reduction opportunities and the possibility of hydrogen production with minimal associated CO₂ emissions;
 - Cost reductions of 55% over BAT at the start of the CCP
 - For situations where syngas must be produced for reasons other than carbon sequestration (for example to make H₂ or to produce power by IGCC), the incremental cost to capture CO₂ can be as low as \$15/t."
 - Process step reduction and H₂ membranes offer significant capital cost reductions and further potential for reducing CO₂ avoided cost in the 2010-2015 perspective.

